

T02 Non-Skid Adhesive (NSA)



CEMENTITIOUS POLYMER MODIFIED TILE ADHESIVE

Description

Roff Non-Skid Adhesive is a blended polymer modified cement based powder tile adhesive. It gives excellent bond on cementitious surfaces like, concrete, plaster, etc. Roff Non-Skid Adhesive forms a waterproof barrier between two surfaces and has excellent 'grab' properties. This is an ideal product for Tile-on-Tile applications.

Areas of Application

For fixing all types of tiles on internal wall/floor, external floor & tile on tile applications.

Features & Benefits

- Ready to use, needs only mixing with water
- Excellent adhesion, low shrinkage
- Suitable for indoor and tile on tile applications
- Sufficiently flexible to accommodate physical & thermal movements
- Needs no curing, needs no hacking or mechanical key on the surfaces
- Floors can be used after 24 hours
- Soaking of tiles & backing of surface not required

Method of Application

- The surface to be tiled should be sound and thoroughly cleaned. Old surface should be free from wax, grease, polish etc.
- Add 3 to 3.5 parts of Roff NSA Powder to 1 part of water. At site, addition of water shall be adjusted to attain desired consistency. Do not put water into the powder. Mix with a trowel / slow speed drills (50 - 100 rpm) until a lump free homogeneous paste is obtained.
- Always mix the required quantity, which can be consumed within the prescribed pot life adopting the mixing proportion mentioned above.
- Leave the mixture for 5 min. before using.
- Spread the adhesive to a thickness of approx. 3-6 mm and comb with a notched trowel. Strictly apply the adhesive paste which can be tiled with in 10 to 15 mins.
- Intermittently touch the adhesive paste on substrate by finger. If the adhesive sticks to fingers then continue tiling and if not scrape off the adhesive and apply new coat.
- Start placing the tiles on the surface to be tiled. Tap the tiles properly to ensure complete coverage of the backside of tiles and to eliminate the possibility of any air voids.
- Keep joints between two-tiles using Tile Spacers
- Allow tiling to set for 24 hours and start filling joints next day with Roff Rainbow Tile Mate.
- After grouting clean and polish tiles with a damp sponge or cloth. To remove Hard Stains use Roff Cera Clean.

Precautions & Limitations

- Always add powder to water and not water to powder.
- Do not add more water than recommended.
- Do not add sand or cement at site.
- Before doing tile-on-tile application, ensure that the original tiling surface is in sound condition.
- In case of undulations in the existing floor, rectify the same before applying Roff Non-Skid Adhesive.
- Strictly not recommended for the direct use on gypsum plaster, paint, wood & metal.

T02 Non-Skid Adhesive (NSA)



CEMENTITIOUS POLYMER MODIFIED TILE ADHESIVE

Technical Information

Appearance	:	Cement Grey Powder
Mix ratio	:	Approx. 3 - 3.5 : 1 (by vol.)
Open time	:	Approx. 10 - 15 minutes at 30°C
Pot life	:	approx. 60 - 90 min. at 30°C
Coverage	:	7 - 7.5 Sq. mtr. / 30 Kg Bag at 3 mm thickness 3 - 3.5 Sq. mtr. / 30 Kg Bag at 6 mm thickness
Trafficable time	:	24 hrs (max.)
Curing time	:	14 days at 30°C
Self Life	:	12 months pack sealed and stored in damproof conditions

Packaging

5 Kg, 10 Kg, 20 Kg & 30 Kg.



Pidilite Industries Limited

Construction Chemicals Division
Ramkrishna Mandir Road
Post Box No. 17411
Andheri (E) Mumbai 400059 INDIA
Tel +91-22-2835 7000 • Fax +91-22-2835 7008
website : www.roff.in • E-mail : roff@pidilite.co.in
Toll Free No.: 1800-209-5504

DISCLAIMER The product information & application details given by the company & its agents has been provided in good faith & meant to serve only as a general guideline during usage. Users are advised to carry out tests & take trials to ensure on the suitability of products meeting their requirement prior to full scale usage of our products. Since the correct identification of the problems, quality of other materials used and the on-site workmanship are factors beyond our control, there are no expressed or implied guarantee / warranty as to the results obtained. The company does not assume any liability or consequential damage for unsatisfactory results, arising from the use of our products.