

# T07 Ply Master



FLEXIBLE ADDITIVE FOR TILE ON WOOD

## Description

**Roff Ply Master** is a flexible additive for use with Roff NSA. It is specially formulated to provide a strong, super flexible bond for tiling on specially exterior grade plywood & most substrates.

## Areas of Application :

Fixing tile & stone on wooden, gypsum, bison, Asbestos & fibre cement substrate for internal / external application in residential as well as commercial areas like shops, malls, club houses, country home etc.

## Features & Benefits

- High bond strength
- Shock resistance with higher flexibility
- Excellent waterproofing characteristics
- Needs no curing and soaking of substrate or tile
- Easy to use
- Non hazardous & non-flammable liquid

## Method of Application

- The surface to be tiled should be sound and thoroughly cleaned. Old surface should be free from wax, grease, polish etc.
- Add 3 to 3.5 parts of Roff NSA Powder to 1 part of Roff Plymaster.
- Mix with a trowel / slow speed drills (50 - 100 rpm) until a lump free homogeneous paste is obtained.
- Always mix the required quantity, which can be consumed within the 60 - 90 min. pot life.
- Leave mixture for 5 min. before using.
- Spread the adhesive to a required bed thickness and comb with a notched trowel. Strictly apply the adhesive paste which can be tiled with in 10 to 15 mins.
- Intermittently touch the adhesive paste on substrate by finger. If the adhesive sticks to fingers then continue tiling and if not scrape off the adhesive and apply new coat.
- Start placing the tiles on the surface to be tiled. Tap the tiles properly to ensure complete coverage of the backside of tiles and to eliminate the possibility of any air voids.
- Keep joints between two-tiles using Tile Spacers.
- Allow tiling to set for 24 hours and start filling joints next day with Roff Rainbow Tile Mate.

## Precautions & Limitations

- Always add powder to liquid and not liquid to powder.
- Do not add more liquid than recommended.
- Do not add sand or cement at site.

# T07 Ply Master



FLEXIBLE ADDITIVE FOR TILE ON WOOD

## Technical Information

Appearance	:	White emulsion
Sp Gravity	:	1.05
Mix ratio	:	Approx. 2.5 : 1 (by vol).
Open time	:	Approx. 15 - 20 minutes at 30°C
Pot life : approx.	:	60 - 90 min. at 30°C
Trafficable time	:	24 hrs (max.)
Self Life	:	12 months pack sealed and stored in damproof conditions
Coverage	:	Approx. 7- 7.5 Sq. mtr. / 10 ltr. of Roff Plymaster mixed with 30 Kg of Roff NSA.

## Packaging

5 Litre & 20 Litre



### Pidilite Industries Limited

Construction Chemicals Division  
Ramkrishna Mandir Road  
Post Box No. 17411  
Andheri (E) Mumbai 400059 INDIA  
Tel +91-22-2835 7000 • Fax +91-22-2835 7008  
website : [www.roff.in](http://www.roff.in) • E-mail : [roff@pidilite.co.in](mailto:roff@pidilite.co.in)  
**Toll Free No.: 1800-209-5504**

**DISCLAIMER** The product information & application details given by the company & its agents has been provided in good faith & meant to serve only as a general guideline during usage. Users are advised to carry out tests & take trials to ensure on the suitability of products meeting their requirement prior to full scale usage of our products. Since the correct identification of the problems, quality of other materials used and the on-site workmanship are factors beyond our control, there are no expressed or implied guarantee / warranty as to the results obtained. The company does not assume any liability or consequential damage for unsatisfactory results, arising from the use of our products.